

SWIFTWALL[®] FLEX

ARE YOU FLEXIBLE?

INTRODUCING SWIFTWALL[®] FLEX

SwiftWall once again advances the temporary barrier market with new SwiftWall Flex, an adjustable height barrier that bridges heights from 4 to 18 feet. The development of SwiftWall Flex advances our goal of simplifying construction while progressing our sustainability initiatives.



SwiftWall Flex is a reusable modular panel system, but now with adjustable height to fit varying ceiling heights with no cutting and frameless finished wall appearance. SwiftWall modular panel systems simply and quickly assemble to create and transform space - temporarily or more permanently - without the mess of drywall.



SWIFTWALL[®] FLEX

Features:

- Adjustable height – no cutting required
- Up to 3.5 ft of adjustment on all standard height panels (4, 8, 10, 12, 16 ft)
- Highest value offering in the adjustable barrier market
- Superior finished wall appearance – framework concealed within finished surface
- Available in ASTM E-84 Class A and C Fire-Rating, ICRA Class IV
- Sliding, adjustable height top panel – use the provided Allen wrench to loosen panels, slide top panel to required height and re-tighten to secure in place
- 4 ft wide panels
- Manufactured with non-hygroscopic materials that do not absorb or retain moisture
- Installs 5x faster than studs and drywall
- Highly durable, very lightweight, stronger than drywall
- Easily install and remove graphics
- Quickly reconfigured, 20+ reuses, sustainable, recyclable

SwiftWall Panels Meet ICRA Class IV Standards

ICRA (Infection Control Risk Assessment) guidelines are used to prevent environment-associated infections in healthcare facilities during any construction or renovation project within patient-occupied or sensitive spaces. SwiftWall temporary wall systems provide negative air capabilities for infection control personnel and contractors that meet ICRA Class IV requirements.

- Aluminum joiners adhere one panel right into the next for a virtually seamless install
- Closed-cell foam core ensures a non-hygroscopic construction
- Product versatility allows for customization to any unique space and application requirement
- Easily disinfect with common disinfectants or cleaners



ASTM E-84 Fire Rating

Healthcare construction or renovations require temporary barriers to meet the ASTM E-84 Class A requirement. SwiftWall's reusable wall systems are tested and listed as meeting ASTM E-84 Class A performance for smoke and flame spread.

In most cases, as per ASHE's NFPA 241 guidelines, a non-one-hour fire-rated temporary separation wall system is permitted when there is a working sprinkler system in place. NFPA 241 8.6.2.4 allows non-rated walls *and* opening protectives when a sprinkler system is installed. If the renovated area has a sprinkler system installed, then the separation wall can be non-rated. We recommend getting approval for this configuration from your AHJ in buildings that are not fully sprinkler protected.

Furthermore, if the sprinkler system needs to be deactivated for any reason, a fire watch protocol must be put in place until such time as the sprinkler system is working again. In these instances, SwiftWall is an excellent temporary barrier per ASHE's NFPA 241 guidelines.

Learn more at [SwiftWall.com/Products](https://www.swiftwall.com/Products).



[SwiftWall.com](https://www.swiftwall.com)

989-279-0232 | sales@swiftwall.com