

# SWIFTWALL<sup>®</sup> FLEX

## ARE YOU FLEXIBLE?

### SWIFTWALL<sup>®</sup> FLEX MODULAR WALL SYSTEM

SwiftWall is advancing the temporary barrier market with SwiftWall Flex, an adjustable height barrier that bridges heights from 4 to 18 feet. SwiftWall Flex advances our goal of simplifying construction while progressing our sustainability initiatives.



SwiftWall Flex is a reusable modular panel system, with adjustable height to fit varying ceiling heights with no cutting and frameless finished wall appearance. SwiftWall modular panel systems simply and quickly assemble to create and transform space - temporarily or more permanently - without the mess of drywall.



# SWIFTWALL® FLEX



## Features:

- Adjustable height – no cutting required
- Up to 2.75 ft of adjustment on standard panel height of 7'6" to 10'3"
- Simple-to-clean, non-microbial surface effortlessly sanitized using a variety of disinfectants
- Screwless system – only an Allen wrench required
- Highest value offering in the adjustable barrier market
- Superior finished wall appearance – framework concealed within finished surface
- Available in ASTM E-84 Class A and C Flame Spread rating, ICRA Class V
- Sliding, adjustable height top panel – use the provided Allen wrench to loosen panels, slide top panel to required height and re-tighten to secure in place
- Multiple width panels
- Manufactured with non-hygroscopic materials that do not absorb or retain moisture
- Installs 5x faster than stud and drywall
- Highly durable, stronger than drywall
- Easily to install and remove graphics
- Quickly reconfigured, reusable, sustainable, recyclable



SWIFTWALL FLEX

## SwiftWall Panels Meet ICRA Class V Standards

ICRA (Infection Control Risk Assessment) guidelines are used to prevent environment-associated infections in healthcare facilities during any construction or renovation project within patient-occupied or sensitive spaces. SwiftWall temporary wall systems meeting ICRA Class V requirements provide negative air capabilities for infection control personnel and contractors.

- Aluminum joiners adhere one panel right into the next for a virtually seamless install
- Closed-cell foam core ensures a non-hygroscopic construction
- Product versatility allows for customization to any unique space and application requirement
- Easily disinfect with common disinfectants or cleaners



DEFINE YOUR  
TERRITORY

## ASTM E-84 Flame Spread Rating

Healthcare construction or renovations require temporary barriers to meet the ASTM E-84 Class A requirement. SwiftWall's reusable wall systems are tested and listed as meeting ASTM E-84 Class A performance for smoke and flame spread.

In most cases, as per ASHE's NFPA 241 guidelines, a non-one-hour, fire-rated, temporary separation wall system is permitted when there is a working sprinkler system in place. NFPA 241 8.6.2.4 allows non-rated walls *and* opening protectives when a sprinkler system is installed. If the renovated area has a sprinkler system installed, then the separation wall can be non-rated. We recommend getting approval for this configuration from your AHJ in buildings that are not fully sprinkler protected.

Furthermore, if the sprinkler system needs to be deactivated for any reason, a fire watch protocol must be put in place until such time as the sprinkler system is working again. In these instances, SwiftWall is an excellent temporary barrier per ASHE's NFPA 241 guidelines.



SwiftWall.com | 989.279.0232